



OAK BACKA

The deep amber hue of this 3-strip oak floor from the Götaland Collection is subtly enhanced by charcoal knots and cracks, creating a classic yet luxurious expression. Occasional saw marks accentuate the floor's natural appearance. Each board is meticulously hand-scraped and carefully brushed to bring out the character of the grain and highlight the texture of the timber. Four-sided bevelling at the edges ensures a classic full plank look and feel.

PRODUCT DETAILS

| | |
|---------------------------|---|
| Article Number | 153N66EK02KW240 |
| Surface treatment | Oil |
| Design features | Bevelled 4-sided, Handscraped, Brushed, Saw marks |
| Dimensions | 2419 x 196 x 15 mm |
| Weight per Package | 22.4 kg |
| Area per Package | 2.84 m ² |
| Area Per Board | 0.474 m ² |

DETAIL DESCRIPTION

Contains knots and all natural colour variations.

COLOUR CHANGE

The colour matures over time

FACTS

| | |
|-----------------------------|---------------------|
| Wood Species | Oak |
| Board | 3-strip |
| Grading | Dynamic |
| Range | Kährs Original |
| Collection | Götaland Collection |
| Resandable | 2-3 times |
| Natural/Stained | Stained |
| Brinell Value | 3,7 |
| Joint | Woodloc® 5S |
| Floor heating | Yes |
| Warranty | 30 years |
| Wear-layer material | Hardwood |
| Wear-layer thickness | 3,5 mm |
| Core material | Pine/Spruce/Alder |
| Thickness | 15 mm |
| Installation method | Floating, Glue-down |
| Surface Colour | Light Brown |

TECHNICAL PROPERTIES

| | | |
|--|-------------|------------------------|
| Moisture content | EN13183 | 7%±2% |
| Minimum Mean Density kg/m³ | | >500 kg/m ³ |
| Reaction To Fire | EN13501-1 | Dfl-s1 |
| Formaldehyde Emission | EN717-1 | E1 |
| Content PCP | CEN/TR14823 | ≤ 5 x 10-6n |
| Breaking Strength N/mm² | EN1533 | NPD |
| Thermal Conductivity | EN12664 | 0,14 W/mK |
| Thermal Resistance R-Value | | .11 (m2K/W) |
| Biological Durability | EN350-2 | Class 1 |
| CARB2 | | Compliant |

CERTIFICATES

