



OAK BODA

The warm, golden tones in this 3-strip oak floor from the Götaland Collection are punctuated by naturally occurring knots and cracks, resulting in a timeless and classic expression. Occasional saw marks accentuate the floor's restored appearance. Each board is meticulously hand-scraped and carefully brushed to bring out the character of the grain and highlight the natural texture of the timber. Four-sided bevelling at the edges ensures a classic full plank look and feel.

PRODUCT DETAILS

Article Number	153N66EK01KW240
Surface treatment	Oil
Design features	Bevelled 4-sided, Handscraped, Brushed, Saw marks
Dimensions	2419 x 196 x 15 mm
Weight per Package	22.4 kg
Area per Package	2.84 m ²
Area Per Board	0.474 m ²

DETAIL DESCRIPTION

Contains knots and all natural colour variations.

COLOUR CHANGE

The colour matures over time

FACTS

Wood Species	Oak
Board	3-strip
Grading	Dynamic
Range	Kährs Original
Collection	Götaland Collection
Resandable	2-3 times
Natural/Stained	Natural
Brinell Value	3,7
Joint	Woodloc® 5S
Floor heating	Yes
Warranty	30 years
Wear-layer material	Hardwood
Wear-layer thickness	3,5 mm
Core material	Pine/Spruce/Alder
Thickness	15 mm
Installation method	Floating, Glue-down

TECHNICAL PROPERTIES

Moisture content	EN13183	7%±2%
Minimum Mean Density kg/m³		>500 kg/m ³
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 x 10 ⁻⁶ n
Breaking Strength N/mm²	EN1533	NPD
Thermal Conductivity	EN12664	0,14 W/mK
Thermal Resistance R-Value		.11 (m ² K/W)
Biological Durability	EN350-2	Class 1
CARB2		Compliant

CERTIFICATES

