



OAK CONCRETE

The natural oil finish and sleek grey stain found on this single-strip maple floor from the Artisan Collection create a refined yet rustic expression. Knots and cracks pepper the boards, adding depth and balancing the bleached wheat highlights. Every board is carefully brushed to bring out the character of the grain and emphasise the natural texture of the wood. Four-sided bevelling at the edges ensures a classic full plank look and feel. Hand-scraping enhances the worn appearance of the floor.

PRODUCT DESCRIPTION		FACTS		TECHNICAL PROPERTIES	
Article Number	151XCDEKFMKW190	Wood Species	Oak	Moisture content	EN13183 7%±2%
Surface treatment	Oil	Board	1-strip	Minimum Mean Density kg/m ³	>500 kg/m ³
Design features	Handscraped, brushed, bevelled 4-sided	Grading	Dynamic	Reaction To Fire	EN13501-1 Dfl-s1
Dimensions	1900 x 190 x 15 mm	Range	Kährs Original	Formaldehyde Emission	EN717-1 E1
Weight per Package	17 kg	Collection	Artisan Collection	Content PCP	CEN/TR14823 ≤ 5 x 10-6n
Area per Package	2.17 m ²	Resandable	2-3 times	Breaking Strength N/mm ²	EN1533 NPD
Area Per Board	0.361 m ²	Natural/Stained	Stained	Thermal Conductivity	EN12664 0,14 W/mK
		Brinell Value	3, 7	Thermal Resistance R-Value	.11 (m2K/W)
		Joint	Woodloc®	Biological Durability	EN350-2 Class 1
		Floor heating	Yes	CARB2	Compliant
		Warranty	30 years		
		Wear-layer material	Hardwood		
		Wear-layer thickness	3, 5 mm		
		Core material	Pine/Spruce lamella		
		Thickness	15 mm		
		Installation method	Floating, glue-down		
		EAN Code	7393969033527		
		Surface Colour	Grey FM		
DETAIL DESCRIPTION					
All naturally occurring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.					
COLOUR CHANGE					
Stained product - noticeable color change over time.					
CERTIFICATES					

