

# OAK MAGGIORE

The black-and-tan colour range in this single-strip floor from the Da Capo Collection results in an extremely rustic expression. The naturally occurring knots and cracks add to the quality of the surface, giving the floor a worn complexion reminiscent of reclaimed timber. Each board is carefully brushed to bring out the quality of the grain and highlight the natural properties of the wood. Two-sided bevelling ensures a classic, full plank look and feel. Every board is meticulously hand-scraped, which emphasises the aged appearance of the floor.

PRODUCT DETAILS		
Article Number	151XDDEKF0KW190	
Surface treatment	Oil	
Design features	Handscraped, Bevelled 2- sided, Brushed	
Dimensions	1900 x 190 x 15 mm	
Weight per Package	19 kg	
Area per Package	2.17 m <sup>2</sup>	
Area Per Board	0.361 m <sup>2</sup>	

# **DETAIL DESCRIPTION**

All naturally occuring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes very large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.

### **COLOUR CHANGE**

Some muting of colour variation to medium, straw brown.

FACTS	
Wood Species	Oak
Board	1-strip
Grading	Expressive
Range	Kährs Supreme
Collection	Da Capo Collection
Resandable	2-4 times
Natural/Stained	Natural
Brinell Value	3,7
Joint	Woodloc®
Floor heating	Yes
Warranty	30 years
Wear-layer material	Hardwood
Wear-layer thickness	3,5 mm
Core material	Pine/Spruce lamella
Thickness	15 mm

Glue-down, Floating

Light Brown F0

#### **TECHNICAL PROPERTIES**

Moisture content	EN13183	7%±2%
Minimun Mean Den	sity kg/m³	>500 kg/m³
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 x 10- 6n
Breaking Strength N/mm²	EN1533	NPD
Thermal Conductivity	EN12664	0,14 W/mK
Thermal Resistance	R-Value	.11 (m2K/W)
Biological Durability	EN350-2	Class 1
CARB2		Compliant

## **CERTIFICATES**









Installation method

**Surface Colour**