



MAISON OAK

The combination of smoking and white oil gives this single-strip oak floor from the Grande Collection a dusky blue finish with pale ashen highlights in the pores. The colour variation between boards is very apparent due to the fully smoked planks. Every board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood. Four-sided bevelling at the edges ensures a classic, full plank look and feel. Each board is meticulously hand-scraped, which enhances the rustic appearance of the floor. This product must be oiled after installation and prior to use.

PRODUCT DESCRIPTION

Article Number	201XABEKFBE280
Surface treatment	Oil
Design features	Brushed, smoked, handscraped, bevelled 4-sided
Dimensions	2800 x 260 x 20 mm
Weight per Package	38 kg
Area per Package	2.91 m ²
Area Per Board	0.728 m ²

DETAIL DESCRIPTION

Naturally occurring wood colour variations allowed, from light to dark brown. The smoked design is likely to enhance the naturally occurring wood color variations and create further contrast between light and dark. The product includes large sound and black knots. Knots may vary in size and numbers. Grande products may continue to develop their rustic nature after the floor has been installed; splits and cracks that occur after installation are normal and should be considered part of the timbers natural character.

COLOUR CHANGE

Smoked product - noticeable color change over time.

FACTS

Wood Species	Oak
Board	1-strip
Grading	Variation (Town)
Range	Kährs Supreme
Collection	Grande Collection
Resandable	2-4 times
Natural/Stained	Stained
Joint	Tongue & Groove
Floor heating	No
Warranty	30 years
Wear-layer material	Hardwood
Wear-layer thickness	5 mm
Backside material	Veneer
Thickness	20 mm
Installation method	Floating, glue-down
EAN Code	7393969031509
Surface Colour	Grey Blue FB

CERTIFICATES



TECHNICAL PROPERTIES

Moisture content	EN13183	7%±2%
Minimum Mean Density kg/m³		>500 kg/m ³
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 x 10-6n
Breaking Strength N/mm²	EN1533	NPD
Thermal Conductivity	EN12664	0,14 W/mK
Thermal Resistance R-Value		.14 (m2K/W)
Biological Durability	EN350-2	Class 1
CARB2		Compliant