



## OAK ATTEBO

The cigarillo brown nuances featured in this 3-strip oak floor from the Götaland Collection are enhanced by flashes of rich charcoal and burnt embers, resulting in a moderately rich colour variation and a refined expression. Occasional saw marks accentuate the floor's restored appearance. Each board is meticulously hand-scraped and carefully brushed to bring out the character of the grain and highlight the natural texture of the timber. Four-sided bevelling at the edges ensures a classic full plank look and feel.

PRODUCT DETAILS		FACTS		TECHNICAL PROPERTIES			
<b>Article Number</b>	153N66EK04KW240	<b>Wood Species</b>	Oak	<b>Moisture content</b>	EN13183 7%±2%		
<b>Surface treatment</b>	Oil	<b>Board</b>	3-strip	<b>Minimum Mean Density kg/m³</b>	>500 kg/m³		
<b>Design features</b>	Bevelled 4-sided, Handscraped, Brushed, Saw marks	<b>Grading</b>	Dynamic	<b>Reaction To Fire</b>	EN13501-1 Dfl-s1		
<b>Dimensions</b>	2419 x 196 x 15 mm	<b>Range</b>	Kährs Original	<b>Formaldehyde Emission</b>	EN717-1 E1		
<b>Weight per Package</b>	22.4 kg	<b>Collection</b>	Götaland Collection	<b>Content PCP</b>	CEN/TR14823 ≤ 5 x 10-6n		
<b>Area per Package</b>	2.84 m²	<b>Resandable</b>	2-3 times	<b>Breaking Strength N/mm²</b>	EN1533 NPD		
<b>Area Per Board</b>	0.474 m²	<b>Natural/Stained</b>	Stained	<b>Thermal Conductivity</b>	EN12664 0,14 W/mK		
<b>DETAIL DESCRIPTION</b>	Contains knots and all natural colour variations.		<b>Brinell Value</b>	3,7	<b>Thermal Resistance R-Value</b>	.11 (m2K/W)	
<b>COLOUR CHANGE</b>	The colour matures over time		<b>Joint</b>	Woodloc® 5S	<b>Biological Durability</b>	EN350-2 Class 1	
		<b>Floor heating</b>	Yes	<b>Warranty</b>	30 years	<b>CARB2</b>	Compliant
		<b>Wear-layer material</b>	Hardwood	<b>Wear-layer thickness</b>	3,5 mm		
		<b>Core material</b>	Pine/Spruce/Alder	<b>Thickness</b>	15 mm		
		<b>Installation method</b>	Floating, Glue-down	<b>Surface Colour</b>	Dark brown		

### CERTIFICATES

