



## OAK ECLIPSE

The mineral grey notes in this 3-strip oak floor from the Lumen Collection are awash with stoney earth tones, eloquently complemented by the ultra-matt lacquer finish. Each board is carefully brushed to perfection to enhance the natural character of the grain. The ultra-matt lacquer finish enhances the natural variations in the wood, creating the impression of newly sawn timber. This effectively eliminates glare while protecting the floor from daily wear.

### PRODUCT DETAILS

<b>Article Number</b>	153N3BEKE4KW240
<b>Surface treatment</b>	Ultra matt lacquer
<b>Design features</b>	Brushed
<b>Dimensions</b>	2423 x 200 x 15 mm
<b>Weight per Package</b>	23 kg
<b>Area per Package</b>	2.91 m <sup>2</sup>
<b>Area Per Board</b>	0.485 m <sup>2</sup>

### DETAIL DESCRIPTION

Even colour with minor variations. Small sized knots in limited numbers allowed.

### COLOUR CHANGE

Stained product - noticeable color change over time

### FACTS

<b>Wood Species</b>	Oak
<b>Board</b>	3-strip
<b>Grading</b>	Variation (Town)
<b>Range</b>	Kährs Original
<b>Collection</b>	Lumen Collection
<b>Resandable</b>	2-3 times
<b>Natural/Stained</b>	Stained
<b>Brinell Value</b>	3,7
<b>Joint</b>	Woodloc® 5S
<b>Floor heating</b>	Yes
<b>Warranty</b>	30 years
<b>Wear-layer material</b>	Hardwood
<b>Wear-layer thickness</b>	3,5 mm
<b>Core material</b>	Pine/Spruce/Alder
<b>Thickness</b>	15 mm
<b>Installation method</b>	Floating, Glue-down
<b>Surface Colour</b>	Grey

### TECHNICAL PROPERTIES

<b>Moisture content</b>	EN13183	7%±2%
<b>Minimum Mean Density kg/m<sup>3</sup></b>		>500 kg/m <sup>3</sup>
<b>Reaction To Fire</b>	EN13501-1	Dfl-s1
<b>Formaldehyde Emission</b>	EN717-1	E1
<b>Content PCP</b>	CEN/TR14823	≤ 5 x 10 <sup>-6</sup> n
<b>Breaking Strength N/mm<sup>2</sup></b>	EN1533	NPD
<b>Thermal Conductivity</b>	EN12664	0,14 W/mK
<b>Thermal Resistance R-Value</b>		.11 (m <sup>2</sup> K/W)
<b>Biological Durability</b>	EN350-2	Class 1
<b>CARB2</b>		Compliant

### CERTIFICATES

